



ovattificio
fortunato
l'anima delle idee

THECNICAL SHEET : EDILKENAF

COMPOSITION:

Mix of natural fibers (kenaf).

FEATURES:

Fiber mat 100% kenaf, thermo bonding. No use chemical binders (resins, adhesives, etc.).

The product has characteristics of thermo-acoustic insulation.

Ecological product, fully recyclable.

It is identified as a function of weight per unit area (g / sqm), in thickness and density (kg / mc).

DIMENSIONS (mm):

1400 x 600 mm Tolerance ± 5

THICKNESS (mm):

40 $\pm 5\%$ Tolerance

Weight (g / sqm):

1600 $\pm 5\%$ Tolerance

DENSITY '(kg / mc):

40 $\pm 5\%$ Tolerance

CONDUCTIVITY 'HEAT:

λ : $0.0353 \frac{W}{m K}$

THERMAL RESISTANCE:

R: $1.133 \frac{m^2 K}{W}$



PACKING:

- Plates in packs of 15 sheets, polythene welded

NB The packing can 'be customized with the brand of the Customer

APPLICATIONS AND finish:

- Not provided

AREAS OF USE:

- Construction

NOTE: Density of product > 40 kg / mc
improve the thermo-acoustic performances of the same.